



FT1 Optional Power Supply

- AC/DC Converter 24V 120W
- For Use with Fox Model FT1 Thermal Mass Flow Meter
- 4" DIN mounting rail provided
- To order specify Fox P/N 106728



Power Supply Features

- Universal AC input voltage range
- Adjustable output
- DC input capable
- IP20
- Load Sharing
- Power will not de-rate for the entire input voltage range
- Power Boost of 150% for 5 seconds
- Full corrosion-resistant aluminum casing
- Extreme low temperature cold start -20°C
- Conformal coating on PCBAs to protect against common dust and chemical pollutants
- Hazardous Locations approval to ATEX
- 4" DIN mounting rail provided

Operating Specs

Number of Outputs: 1

Output Voltage: 24V

Output Current (Max): 5.00A

Output Power Watts (Max): 120W

Input Voltage Range: 85-264Vac (DC Input range 120-375VDC)

Voltage Isolation: 4kV (4000V)

Phase Input: Single Phase

Operating Temperature: -20°C ~85°C (With Derating)

Physical Specs

Mounting Type: DIN Rail

Dimensions (L x W x D):

4.6" x 1.97" x 4.85" (121 x 50 x 123.1 mm)

Material: Metal case, Lead free / RoHS Compliant

Approvals

CB, CE, CSA, UL



399 Reservation Road
Marina, CA 93933

Phone: (831) 384-4300

Fax: (831) 384-5786

sales@foxthermalinstruments.com

www.foxthermalinstruments.com